


S Series

Surface Mount Speakers



S15

Rear Panel




S15W



S55

Rear Panel



Advanced surface mount speakers for a wide range of applications.


- "Wide waveguide horn" produces an ideal spherical wave that delivers consistent acoustic energy and flat frequency response over a broad area.
- Advanced two-way design employs high-quality components for smooth, flat response. Emphasis on natural reproduction has resulted in luxurious lows and an extended high-frequency range. Clean, well-balanced sound even at low volume in any installation.
- Both woofer and tweeter are high input capacity units designed for extended reliability. A protection circuit is also provided.
- Wedge design blends with sophisticated interior décor, and a three-layer finish projects a sense of quality.
- The S15 and S55 can be positioned vertically or horizontally. A variety of installation brackets are available as options.
- White and black models available. Sold in pairs. (S15)

OPTIONS

BCS20-150/210
Ceiling Bracket



BWS20-120/190
Wall Bracket



BAS10
Free-Angle Clamp
for S15



BMS-10A
Mic Stand Adaptor
for S15




GENERAL SPECIFICATIONS

Model	S15 / S15W	S55
Frequency range	65Hz-40kHz	60Hz-40kHz
Power rating	PGM 80W	140W
	MAX 160W	250W
Nominal impedance	6Ω	6Ω
Sensitivity (1W/1m)	88dB SPL	90dB SPL
Dispersion	120°	120°
Crossover Frequency	3.5kHz	2.5kHz
Others	Protection (Tweeter)	Protection (Tweeter)
Components	LF: 12cm (5") cone, HF: 2.5cm (1") + Wave-guide horn	LF: 16cm (6.5") cone, HF: 2.5cm (1") + Wave-guide horn
Enclosure	Bass-reflex type	Bass-reflex type
Input Terminal	Push terminal x 1	Push terminal x 1
Dimensions (W x H x D)	241 x 160 x 145mm (9.5" x 6.3" x 5.7")	370 x 250 x 215mm (14.6" x 9.8" x 8.5")
Weight	2.8Kg (6.17lbs)	6.0Kg (13.2lbs)

DIMENSIONS

unit : mm

S15 / S15W



S55

